

Safety Data Sheet



1. Identification of the substance/mixture and supplier

Product Name: Bondurox Super C
Other Names:
Recommended use: Polyurethane Adhesive (moisture cure)
Supplier: Uroxsys Ltd
Street Address: 2 Stonedon Drive, East Tamaki, Auckland
Telephone Number: +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)
Facsimile: +64 9 2740500
Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference:
Uroxsys Helpline
National Poison Information Centre 0800 POISON (764766)
Date of issue 21st August 2013

2. Hazards identification

DANGER



6.1D(Inhalation), 6.3A, 6.4A, 6.5A, 6.5B, 6.9A, 6.9(Respiratory), 9.3A

EPA Approval:HSR002670.

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006

Hazard Statements:

- Harmful if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- Causes damage to organs through prolonged or repeated exposure
- May cause respiratory irritation.
- Very toxic to terrestrial vertebrates.

Prevention Statements

- Keep out of reach of children.
- Read label before use.
- Avoid breathing fume/gas/mist/vapours.
- Use only outdoors or in a well-ventilated area.
- Wash hands thoroughly after handling.
- Wear protective gloves/eye protection/face protection.
- Avoid breathing fume/gas/mist/vapours.
- In case of inadequate ventilation wear respiratory protection. (See section 8)
- Contaminated work clothing should not be allowed out of the workplace.
- Do not eat, drink or smoke when using this product.
- Avoid release to the environment.

Response Statements

- If medical advice is needed, have product container or label at hand.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- IF ON SKIN: Wash with plenty of soap and water.
- Take off contaminated clothing and wash before re-use.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- If skin irritation or rash occurs: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.
- Collect spillage.

3. Composition/information on ingredients

Material	CAS No	Content %
IsocyanatePrepolymer		30 – 60
Methylene, 4,4'-diphenyl diisocyanate-	101-68-8	10 – 30
Propylene carbonate	108-32-7	< 10
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	< 10
Polymethylenepolyphenylisocyanate	9016-87-9	< 10
Non-hazardous materials		Balance

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion: Immediately rinse mouth with water. Give plenty of water to drink. If vomiting occurs give further water. Seek medical assistance.

Inhalation: Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give

oxygen through a face mask. Apply artificial respiration if patient is not breathing. Get to a hospital or doctor quickly.

Skin Contact: Wipe material from skin with cloth or absorbent paper. Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If swelling, redness, blistering, or irritation occurs seek medical advice. Traces of cured material (after water contact) is not considered hazardous. Do NOT remove with solvent. Allow to peel off naturally or hasten by soaking in tepid to warm water.

Eye Contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Remove clothing is contaminated and wash skin. Seek immediate medical assistance.

Notes to physician:

Treat symptomatically. Effects may be delayed.

5. Fire-fighting measures

Hazards from combustion: On burning may emit toxic fumes including those of carbon oxides, nitrogen oxides, isocyanate vapours and hydrogen cyanide.

Fire-fighting advice: Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media: Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder)

6. Accidental release measures

Emergency procedures: If contamination of sewers or waterways has occurred advise local emergency services.

Methods for containment & clean up:

For small spills: Quickly wipe up material before it cures, with cloth or absorbant paper avoiding skin contact. Uncured material will dissolve in acetone or acetone based nail polish remover. Cured material can only be removed by abrasion.

For large spills: Wear protective equipment to prevent skin and eye contamination and inhalation of vapours. Scrape up material before it cures. Collect and seal in properly labeled containers for disposal. Wash area down with excess water. Cured material can only be removed by abrasion.

7. Handling and storage

Handling advice: Avoid skin and eye contact.

Storage advice: Store in a cool place and out of direct sunlight. Store away from acids, alcohols, oxidizing agents, moisture and sources of heat or ignition. Keep dry, reacts with water; may lead to drum rupture. Keep containers closed at all times, check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

Isocyanates, all (as-NCO): TWA 0.02 mg/m³; STEL 0.07 mg/m³, sen, NZ

As published by the New Zealand Occupational Safety and Health Service (OSH)

TWA (Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

STEL (Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight hour, time-weighted average exposures should be determined.

‘Sen’ Notice – sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated area. Keep containers closed when not in use.

Personal Protective Equipment:

Avoid skin and eye contact and inhalation of vapour or spray. Wear overalls, safety boots, full-face visor and general purpose gloves (PVC). Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Brown thixotropic paste
Solubility:	Insoluble in water.
Specific Gravity:	1.2
Flash Point (°C):	>100°C (closed cup)
Flammability Limits (%):	not available
Boiling Point/Range (°C):	>208

10. Stability and reactivity

Stability: Stable under normal conditions

Conditions to avoid: Avoid contact with foodstuffs.

Incompatible materials: Reacts with alcohols, acids, oxidizing agents and moisture

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea and abdominal pain.

Eye contact: An eye irritant.

Skin contact: Contact with skin may result in irritation. May cause skin sensitization in sensitive individuals. Repeated or prolonged skin contact may lead to allergic contact dermatitis. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including diisocyanates.

Inhalation: A respiratory irritant and potential respiratory sensitiser. Repeated inhalation of vapour or spray mists at levels above the occupational exposure standard could cause respiratory sensitization. Symptoms may include irritation of the eyes, nose, throat and lungs, possibly with dryness of the throat, tightness of the chest and difficulty breathing. Onset of respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response may develop to even minimal concentrations of MDI in sensitized individuals.

Long Term Effects:

There are reports that chronic exposure to isocyanates by inhalation, may result in a permanent decrease in lung function.

Toxicological Data:

No LD50 data available for the product. However, for constituent MDI products:

Oral LD50 (rat): >15000 mg/kg, Inhalation LC50 (rat): 490 mg/m³ (aerosol)

12. Eco toxicological information

Avoid contaminating waterways. Material is practically non-toxic to aquatic organisms on an acute basis.

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Empty container: Do not contaminate storm water with product or product washing. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well-ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via domestic recycling programmes may differ between local authorities. Check with your local council first.

14. Transport information

Road and Rail Transport

Not classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. Regulatory information

EPA Approval:HSR002670.

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006

16. Other information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS