



## TECHNICAL DATA

### D-VISE STANDARD POLYURETHANE ADHESIVE

<b>DESCRIPTION</b>	A single pack moisture curing polyurethane based adhesive.
<b>USES</b>	Bonding wood to wood, MDF, stone, metal, ceramics and some plastics.
<b>COLOUR</b>	Clear amber liquid
<b>FEATURES</b>	Excellent bond strength Rapid cure Good wet grab and initial hold Low smell
<b>SURFACE PREPARATION</b>	All surfaces must be clean, dust free and tight fitting. For glossy surfaces, sand to provide a key. It is preferable that one of the surfaces to be bonded is porous to allow the moisture required for curing to migrate to the glue line.
<b>APPLICATION</b>	1. Apply adhesive to one surface at the joint and then clamp until bond is secure (approximately 30-60 minutes). 2. Faster cure can be achieved by lightly dampening the unglued surface before making the join. 3. Some dense timbers will benefit by having both bonding surfaces precleaned with a damp cloth to help open timber pores before gluing.

## TECHNICAL DATA

<b>Packaging:</b>	500ml and 1 litre plastic bottles.
<b>Specific Gravity:</b>	1.12
<b>Viscosity:</b>	4600-6600 cps (Bf 3/10/25)
<b>Coverage Rate:</b>	1 ½ -2 m <sup>2</sup> per litre, dependent on end use.
<b>Cure Time:</b>	Normally for wood substrate cure time is about 4 hours.
<b>Working Time:</b>	Approximately 30 minutes once applied, depending on ambient conditions.
<b>Shelf Life:</b>	Six months in unopened containers. Opened cans may skin and this may be cut off and remaining product used.
<b>Clean Up:</b>	Clean up frequently using Uroxsys Polyurethane Brush Cleaner before product has set on equipment.
<b>SAFETY DATA:</b>	Wear protective clothing. <b>Gloves are essential</b> , as product bonds well to skin. For further information refer to material safety data sheet.

This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

DVISE TD3 MAR14