

# Safety Data Sheet



## 1. Identification of the substance/mixture and supplier

|                                    |   |
|------------------------------------|---|
| Product Name:                      | Polyurethane Adhesion Promoter  |
| Other Names:                       | Silane Primer   |
| Recommended use:                   | Adhesion promoter primer coat for glass and concrete                                |
| Supplier:                          | Uroxsys Ltd   |
| Street Address:                    | 2 Stonedon Drive, East Tamaki, Auckland   |
| Telephone Number:                  | +64 9 2740808 (8.00am to 5.00pm, Monday to Friday)                                  |
| Facsimile:                         | +64 9 2740500   |
| Emergency Telephone:               | After hours phone 0800 867666 (or 09 3034580), quote reference:<br>Uroxsys Helpline |
| National Poison Information Centre | 0800 POISON (764766)  |
| Date of issue                      | 6 May 2019  |

## 2. Hazards identification



### DANGER

3.1B, 6.1E (Oral), 6.3B, 6.4A

EPA Approval: HSR002662 Surface Coatings and Colourants (Flammable) Group Standard 2017  
Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

### Hazard Statements:

H225 Highly flammable liquid and vapour.  
H303 May be harmful if swallowed  
H316 Causes mild skin irritation.  
H319 Causes serious eye irritation.

### Prevention Statements

P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.

P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/eye protection.

### Response Statements

P101 If medical advice is needed, have product container or label at hand.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P322+P313 If skin irritation occurs: Get medical advice/ attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder for extinction.

### Storage Statements

P403+P235 Store in a well-ventilated place. Keep cool.

### Disposal Statements

P501 Do not let product enter the environment. Do not dispose of in waterways or sewers. Unwanted product should be brushed out on newspaper, allowed to cure and then disposed of via waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

## 3. Composition/information on ingredients

| Material                                 | CAS No    | Content % |
|--|-----------|-----------|
| Isopropyl alcohol                        | 67-63-0   | > 70      |
| Gamma-methacryloxypropyltrimethoxysilane | 2530-85-0 | < 2       |
| Gamma-aminopropyltriethoxysilane         | 919-30-2  | < 1       |

## 4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

**Ingestion:** Do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.  
**Inhalation:** Remove to fresh air. If respiratory irritation, dizziness, nausea or unconsciousness occurs seek medical attention  
**Skin Contact:** Wash skin thoroughly with water. Launder contaminated clothing before re-use.  
**Eye Contact:** Flush eye with water. If irritation persists obtain medical attention.  
**Advice to Doctor:**  
Treat symptoms with reference to specific health effects identified above.

## 5. Fire-fighting measures

**Specific Hazards:** Highly Flammable liquid. On burning will emit toxic fumes including those of oxides of carbon.

**Fire-fighting advice:** On burning will emit toxic fumes. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:** Foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem Code:** 3[Y]E

## 6. Accidental release measures

### Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

### Methods for containment & clean up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers or drums for disposal.

## 7. Handling and storage

**Handling advice:** Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to a source of ignition and flash back.

**Storage advice:** Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. Exposure controls/personal protection

### Occupational Exposure Limits:

No value assigned for this specific material by Worksafe NZ. However, NZ Workplace Exposure Standard(s) for constituent(s):

Isopropyl alcohol: TWA is 400 ppm (983mg/m<sup>3</sup>), STEL is 500 ppm (1230mg/m<sup>3</sup>)

### Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.

**Personal Protective Equipment:**

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

**9. Physical and chemical properties**

Physical state: Liquid  
Colour: colourless  
Solubility: slightly  
Specific Gravity: 0.8  
Flash Point (°C): 12°C  
Flammability Limits (%): 2.3-12.7  
Boiling Point/Range (°C): 82°C

**10. Stability and reactivity**

**Stability:** Stable under normal conditions

**Conditions to avoid:** Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition and open flame

**Incompatible materials:** Incompatible with oxidising agents

**Hazardous decomposition**

**products:** Combustion will generate oxides of carbon

**11. Toxicological information**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** Practically non toxic.  
**Eye contact:** Practically non irritating.  
**Skin contact:** Practically non irritating.  
**Inhalation:** Practically non toxic.

**Supplementary Information:**

Prolonged, repeated skin contact may result in skin irritation. Prolonged, repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Respiratory irritation, dizziness, nausea, loss of consciousness.

**Toxicological Data:**

No LD50 data available for the product. However, for constituent isopropyl alcohol:  
Oral LD50 (mouse): 3600 mg/kg

## 12. Eco toxicological information

Avoid contaminating soil and waterways

## 13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

Do not let product enter the environment. Do not dispose of in waterways or sewers. Unwanted product should be brushed out on newspaper, allowed to cure and then disposed of via waste collection. Empty containers should be left open in a well-ventilated area to cure. When cured, recycle the container via recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

## 14. Transport information



### Road and Rail Transport

Classified as Dangerous Goods by NZS 5433 Transport of Dangerous Goods on Land.

UN No: 1263

Class-primary 3 Flammable Liquid

Packing Group: II

Proper Shipping Name: PAINT RELATED MATERIAL

Hazchem Code: 3[Y]E

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: II

Proper Shipping Name: PAINT RELATED MATERIAL

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA)

Dangerous Goods Regulations for transport by air.

UN No: 1263

Class-primary: 3 Flammable Liquid

Packing Group: II  
Proper Shipping Name: PAINT RELATED MATERIAL

## **15. Regulatory information**

EPA Approval: HSR002662  
Surface Coatings and Colourants (Flammable) Group Standard 2017

## **16. Other information**

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.

This version replaces all previous versions.

END OF SDS