



TECHNICAL DATA

REDUCER R122

DESCRIPTION	A high flash point solvent blend.	
USES	<ul style="list-style-type: none">- For thinning Duracoat moisture-cured polyurethanes as directed.- For final cleaning and surface sensitisation when recoating aged moisture cured finishes.	
COLOUR	Clear	
FEATURES	Mild odour Xylene free Flash point above normal room temperature Excellent solvency	
APPLICATION	Use as directed on Duracoat MCL Gloss, MCL Satin, MCR Gloss and MCR Satin labels.	
TECHNICAL DATA	Appearance:	Colourless liquid
	Specific Gravity:	0.92
	Flash Point:	45°C
	UN No.:	1263
	DG Class:	3
	Haz. Chem Code:	3Y
	Toxic Substances Schedule:	Standard Poison
	Packaging:	1, 4l, 20l, 200l
SAFETY DATA:	Flammable liquid. Use in well ventilated areas only. Can defat skin and cause irritation. For detailed information, consult the Material Safety Data Sheet, available on request from Uroxsys Ltd or on our web site www.uroxsys.co.nz .	

DISCLAIMER: This information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

R122,TD4 MAR14