

Material Safety Data Sheet

1. Identification of the substance/mixture and supplier

Product Name: **Duracrete System SL Resin, SST Resin**

Recommended use: Epoxy resin

Supplier: Uroxsys Ltd

Street Address: 2 Stonedon Drive, East Tamaki, Auckland

Telephone Number: +64 9 2740808

Facsimile: +64 9 2740500

Emergency Telephone: After hours phone 0800 867666 (or 09 3034580), quote reference: Uroxsys Helpline

Date: 17/05/2017

2. Hazards identification

WARNING

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001



DG Classes: 6.1D (oral, dermal, inhalation), 6.3A, 6.5B, 6.6B, 9.1B
Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006
The HSNO Approval Number for this Group Standard is HSR002670.

Hazard Statements:

- Harmful if swallowed.
- Harmful in contact with skin.
- Causes skin irritation.
- Harmful if inhaled.
- May cause an allergic skin reaction.
- Suspected of causing genetic defects ...
- Toxic to aquatic life with long lasting effects.

Prevention Statements:

- Keep out of reach of children.
- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid breathing /fume/gas/vapours/spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective gloves/eye protection.

Response Statements

- If medical advice is needed, have product container or label at hand.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Take off contaminated clothing and wash before re-use.
- Collect spillage

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth
- IF ON SKIN: Wash with plenty of soap and water.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF exposed or concerned: Get medical advice/ attention.
- If skin irritation or rash occurs: Get medical advice/attention.

Storage Statements

- Store locked up.

3. Composition/information on hazardous ingredients

Bisphenol A/epichlorohydrin	25085-99-8	>60%	R36/38,R43,R51/53
Cresyl glycidyl ether	26447-14-3	10-30%	R36/38,R43

4. First-aid measures

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

Ingestion: If swallowed, do not induce vomiting. Seek medical assistance.

Inhalation: Remove victim from area of exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered.

Skin Contact: If skin contact occurs, immediately remove contaminated clothing and wash skin thoroughly using soap if available. If irritation occurs seek medical advice.

Eye Contact: Immediately flush eyes with water for at least 15 minutes and see a doctor.

Notes to physician:

Treat symptomatically. If skin sensitization has developed and causal relationship has been confirmed, further exposure should not be allowed.

5. Fire-fighting measures

Specific Hazards: Not classified as flammable but will burn. Carbon monoxide may be evolved if incomplete combustion occurs.

Fire-fighting advice: Fire fighters to wear self-contained breathing apparatus and suitable protective clothing. Keep adjacent containers cool by spraying with water.

Suitable Extinguishing Media:

Carbon dioxide, dry chemical, foam or water fog.

Hazchem Code: 2X

6. Accidental release measures

Emergency procedures: If contamination of sewers or waterways has occurred advise local emergency services.

Methods for containment & clean up:

For small spills: Avoid accidents, clean up immediately. Wear protective equipment to prevent skin & eye contact. Wipe up with rag or absorbent paper.

For large spills: Wear protective equipment to prevent skin and eye contamination and inhalation of vapours. Contain - prevent runoff into drains and

waterways. Use absorbent material (sand or earth). Collect and seal in properly labeled containers for disposal.

7. Handling and storage

Handling advice: Avoid contact with skin and eyes and clothing. Avoid breathing vapours. No smoking, open flames or sources of ignition in handling and storage areas. Electrically ground all equipment.

Storage advice: Keep container tightly closed and dry. Store at ambient temperatures.

8. Exposure controls/personal protection

Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH).

Engineering Control Measures:

Ensure ventilation is adequate.

Personal Protective Equipment:

Wear overalls, chemical goggles and rubber gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. Physical and chemical properties

Physical state:	Clear liquid
Colour:	Pale yellow
Solubility:	Negligible
Specific Gravity:	1.1
Flash Point (°C):	125°C
Flammability Limits (%):	not available
Boiling Point/Range (°C):	170°C

10. Stability and reactivity

Stability: Stable at normal temperatures and storage conditions. Reacts with strong oxidizing agents.

Hazardous decomposition products: Not expected to form any during normal storage.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Single dose oral toxicity is considered to be extremely low.

Eye contact: Slightly irritating to eyes.

Skin contact: Slightly irritating to skin. Repeated exposure may cause skin irritation. Has caused allergic skin reaction in humans.

Inhalation: Vapours are unlikely due to physical properties.

Long Term Effects:

Prolonged or repeated exposure may cause skin sensitization.

Toxicological Data:

No LD50 data available for the product.

However, for constituent Bisphenol A/epichlorhydrin:

Oral LD50 (rat) >5000 mg/kg, Dermal LD50 (rabbit) >20000 mg/kg

12. Ecotoxicological information

Avoid contaminating waterways. Not readily biodegradable. Has the potential to bioaccumulate. If product enters soil, it will be mobile and may contaminate groundwater. Toxic to aquatic organisms. Acute toxicity – fish; Toxic, 1>LC/EC/IC 50 <= 10 mg/l.

13. Disposal considerations

Incineration through a licensed waste contractor. If not possible then refer to Waste Management Authority.

14. Transport information**Road and Rail Transport**

Classified as Dangerous Goods by NZS 5433:1999 Transport of Dangerous Goods on Land

UN No.: 3082

Class: 9

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (EPOXY RESIN)

Hazchem: 2X

Packing Group: III

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.: 3082

Class: 9

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (EPOXY RESIN)

Packing Group: III

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No.: 3082

Class: 9

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (EPOXY RESIN)

Packing Group: III

15. Regulatory information

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

Subclass 6.3 Category A - Substances that are irritating to the skin

Subclass 6.4 Category A - Substances that are irritating to the eye

Subclass 6.5 Category B - Substances that are contact sensitisers

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment

16. Other information

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Uroxsys Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Uroxsys Limited at the contact details on page 1.

While Uroxsys Ltd believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Uroxsys Ltd assumes legal responsibility.